







STRONGROOM DOOR ATI III



5	SECURITY LEVEL	Class III according to EN 1143-1 certified by ECB-S and VdS		
0	DESIGN	Door: Multi-walled Hinges: External Door opening angle: 180° Handle/fitting: Protruding 65 mm Door opening inwards		
9	LOCKING	High security double-bit key lock 2 keys (190 mm)		
6	PAINTING	Light gray, RAL 7035 (special paint according to RAL colors for an extra charge)		
	INSURABLE	Individual agreement		



STRONGROOM DOOR ATI III



Model	External di _{Height}	m. in mm ^{Width}	Wall openi Height	ng in mm ^{Width}	Door ligh Height	n t in mm Width	Weight (Kg)
ATi III-18B	1790	860	1800	880	1685	650	706
ATi III-20B	1990	960	2000	980	1885	750	790
ATi III-22B	2190	960	2200	980	2085	750	880
ATi III-18E	1820	920	1800	880	1685	650	706
ATi III-20E	2020	1020	2000	980	1885	750	790
ATi III-22E	2220	1020	2200	980	2085	750	880

B = block frame, E = corner frame

Fittings protrude 65 mm

The corner frame is standard on all AT (i) doors.

The frame depth (= wall thickness) is 240 mm as standard. Special dimensions are possible. For wall thicknesses less than 180 mm, fastening by screwing through the frame bushes is not recommended.

ę	LOCKI	NG OPTIONS					
		Standardlocking	Optional locking systems				
	Model	Double-bit key lock	Mechanical combination lock	Electronic combination lock	Electronic combination lock*	Double lock** (2 Double-bit key locks)	
	ATi III-18B						
	ATi III-20B		•	•	•		
	ATi III-22B						
	ATi III-18E						
	ATi III-20E		•				
	ATi III-22E						

* with emergency key ** other lock combinations possible

ACCES	ACCESSORIES FOR EXTRA CHARGE						
Model	Day-door	Electric emergency opening from the inside with ELO Basic (only possible if ELO Basic equipped)	Inner blockage system	Left door hinge			
ATi III-18B		-					
ATi III-20B	•	-	-	•			
ATi III-22B	•	-	-	•			
ATi III-18E							
ATi III-20E		-					
ATi III-22E							

STRONGROOM DOORS

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.

Müller Safe GmbH In der Hirtenwiese 6 35745 Herborn, Germany www.mueller-safe.de

