



MÜLLER
SAFE



STRONGROOM DOORS



**MÜLLER
SAFE**

STRONGROOM DOOR **ATi II**



Model ATi2-22E



SECURITY LEVEL

Class II according to EN 1143-1
certified by ECB-S



DESIGN

Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Protruding 65 mm
Door opening inwards



LOCKING

High security double-bit key lock
2 keys (150 mm)



PAINTING

Light gray, RAL 7035
(special paint according to RAL colors for an extra charge)



INSURABLE

Individual agreement



STRONGROOM DOORS

STRONGROOM DOOR ATi II



Model	External dim. in mm		Wall opening in mm		Door light in mm		Weight (Kg)
	Height	Width	Height	Width	Height	Width	
ATi II-18B	1790	860	1800	880	1650	670	440
ATi II-20B	1990	960	2000	980	1850	770	540
ATi II-22B	2190	960	2200	980	2050	770	595
ATi II-18E	1820	920	1800	880	1650	670	440
ATi II-20E	2020	1020	2000	980	1850	770	540
ATi II-22E	2220	1020	2200	980	2050	770	595

B = block frame, E = corner frame

Fittings protrude 65 mm

The corner frame is standard on all AT (i) doors.

The frame depth (= wall thickness) is 240 mm as standard. Special dimensions are possible. For wall thicknesses less than 180 mm, fastening by screwing through the frame bushes is not recommended.



LOCKING OPTIONS

Model	Standardlocking		Optional locking systems		
	Double-bit key lock	Mechanical combination lock	Electronical combination lock	Electronical combination lock*	Doppelverschluss** (2 Double-bit key locks)
ATi II-18B	■	■	■	■	■
ATi II-20B	■	■	■	■	■
ATi II-22B	■	■	■	■	■
ATi II-18E	■	■	■	■	■
ATi II-20E	■	■	■	■	■
ATi II-22E	■	■	■	■	■

* with emergency key ** other lock combinations possible



ACCESSORIES FOR EXTRA CHARGE

Model	Day-door	Electric emergency opening from the inside with ELO Basic (only possible if ELO Basic equipped)	Inner blockage system	Left door hinge
ATi II-18B	■	■	■	■
ATi II-20B	■	■	■	■
ATi II-22B	■	■	■	■
ATi II-18E	■	■	■	■
ATi II-20E	■	■	■	■
ATi II-22E	■	■	■	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



STRONGROOM DOORS

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

