



MÜLLER
SAFE



KEY SAFES

KEY SAFE STZ



Model STZ 140



SECURITY LEVEL

S2 according to EN 14450
B according to VDMA 24992 (Conditions May '95)



DESIGN

Body: Double-walled
Door: Double-walled
Hinges: Internal
Door opening angle: 90°
Safes with pull-out partitions, hook bars continuously adjustable

Also available as a version for car keys (longer hooks).



LOCKING

High security double-bit key lock
2 keys (65 mm)



PAINTING

Anthracite gray, RAL 7016



KEY SAFE STZ



Model	External dim. in mm			Number Hooks	Number Partition wall	Door 1 / 2 leaf	Mounting holes		Weight (Kg)
	Höhe	Breite	Tiefe				Backwall	Floor	
STZ 60	450	450	200	60	0	1-leaf	4	0	31
STZ 100	600	450	200	100	0	1-leaf	6	0	38
STZ 140	800	450	200	140	0	1-leaf	6	0	46
STZ 200	600	450	250	200	1*	1-leaf	6	0	43
STZ 280	800	450	250	280	1*	1-leaf	6	0	52

* Swivel panel, ** key panels on telescopic extension



LOCKING OPTIONS

Model	Standardlocking	Optional locking systems
		 Double-bit key lock
STZ 60	■	■
STZ 100	■	■
STZ 140	■	■
STZ 200	■	■
STZ 280	■	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



KEY SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

