



**MÜLLER
SAFE**



FIREPROOF SAFES FOR DOCUMENTS

FIREPROOF SAFE PEW



Model PEW 80



SECURITY LEVEL

Class I according to EN 1143-1
certified by VdS



FIRE RATING

S 60 P according to EN 1047-1



DESIGN

Body: Multi-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Protruding 65 mm
Mounting holes: 1 fixing hole in the floor



LOCKING

High security double-bit key lock
2 keys (120 mm)



PAINTING

Light gray, RAL 7035
(special painting according to RAL colors for an extra charge)



INSURABLE

Individual agreement



FIREPROOF SAFE PEW



Model	External dim. in mm			Internal dim. in mm			Door light		Number Shelves	Door 1 / 2-leaf	Number Files	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width					
PEW 37	379	589	471	278	477	329	263	454	1	1-leaf	3	44	128
PEW 48	482	589	471	381	477	329	366	454	1	1-leaf	6	60	144
PEW 61	615	589	471	514	477	329	499	454	2	1-leaf	6	81	170
PEW 80	801	589	471	700	477	329	685	454	2	1-leaf	12	110	215
PEW 113	1137	704	471	1036	592	329	1021	569	3	1-leaf	21	202	330
PEW 132	1322	704	471	1221	592	329	1206	569	3	1-leaf	21	238	365
PEW 150	1507	704	471	1406	592	329	1391	569	3	1-leaf	28	274	395
PEW 155	1550	886	545	1449	774	403	1434	751	3	1-leaf	40	452	509
PEW 170	1700	886	545	1599	774	403	1584	751	4	1-leaf	44	499	547
PEW 1881	1884	886	545	1783	774	403	1768	751	4	1-leaf	50	556	586
PEW 1882/2	1884	975	559	1783	863	393	1768	845	4	2-leaves	55	604	701
PEW 1883/2	1884	975	696	1783	863	530	1768	845	4	2-leaves	55	815	759
PEW 1884/2	1884	1128	559	1783	1016	393	1768	998	4	2-leaves	65	712	790
PEW 1885/2	1884	1128	696	1783	1016	530	1768	998	4	2-leaves	65	960	851
PEW 1886/2	1884	1282	459	1783	1170	293	1768	1152	4	2-leaves	75	611	839
PEW 1887/2	1884	1282	559	1783	1170	393	1768	1152	4	2-leaves	75	820	886
PEW 1888/2	1884	1282	696	1783	1170	530	1768	1152	4	2-leaves	75	1106	951

Fittings protrude 65 mm



LOCKING OPTIONS

Standardlocking	Optional locking systems		
Double-bit key lock	Mechanical combination lock	Electronic combination lock	Electronic combination lock*

Options for the entire series possible

* with emergency key



ACCESSORIES FOR EXTRA CHARGE

Model	Inner safe Height=200 mm	Inner safe Height=250 mm	Inner safe Height=350 mm 2-leaf	Left door hinge	Additional shelf	Suspension file on telescopic rails	Shelf for hanging files	Special fixing kit for concrete floor
PEW 37	☐	☐	☐	☒	☒	☒	☒	☒
PEW 48	☒	☐	☐	☒	☒	☒	☒	☒
PEW 61	☒	☐	☐	☒	☒	☒	☒	☒
PEW 80	☐	☒	☐	☒	☒	☒	☒	☒
PEW 113	☐	☒	☐	☒	☒	☒	☒	☒
PEW 132	☐	☒	☐	☒	☒	☒	☒	☒
PEW 150	☐	☒	☐	☒	☒	☒	☒	☒
PEW 155	☐	☒	☐	☒	☒	☒	☒	☒
PEW 170	☐	☒	☐	☒	☒	☒	☒	☒
PEW 1881	☐	☒	☐	☒	☒	☒	☒	☒
PEW 1882/2	☐	☐	☒	☐	☒	☒	☒	☒
PEW 1883/2	☐	☐	☒	☐	☒	☒	☒	☒
PEW 1884/2	☐	☐	☒	☐	☒	☒	☒	☒
PEW 1885/2	☐	☐	☒	☐	☒	☒	☒	☒
PEW 1886/2	☐	☐	☒	☐	☒	☒	☒	☒
PEW 1887/2	☐	☐	☒	☐	☒	☒	☒	☒
PEW 1888/2	☐	☐	☒	☐	☒	☒	☒	☒

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



FIREPROOF SAFES FOR DOCUMENTS

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

