



MÜLLER
SAFE



DEPOSIT/BANK EQUIPMENT

DEPOSIT SAFE MD II



Model MD II-130V



SECURITY LEVEL

Class D-II according to EN 1143-2
certified by ECB•S



DESIGN

Body: Multi-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Protruding 35 mm
Mounting holes: 4 fixing holes in the floor, 1 in the backwall*
(*not drilled through)



LOCKING

High security double-bit key lock
2 keys (120 mm)



PAINTING

Light gray, RAL 7035
(special painting according to RAL colors for an extra charge)



INSURABLE

Individual agreement



DEPOSIT SAFE MD II



Model	External dim. in mm			Internal dim. in mm			Door light		Drawer	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width		
MD II-95V	950	590	550	265	480	390	498	474	front	284
MD II-130V	1300	590	550	615	480	390	848	474	front	356
MD II-95R	950	590	550	265	480	390	498	474	on the back	283
MD II-130R	1300	590	550	615	480	390	848	474	on the back	356
MD II-95	950	590	550+270	265	480	390	498	474	protruding 270mm on the back	328
MD II-130	1300	590	550+270	615	480	390	848	474	protruding 270mm on the back	401

Fittings protrude 35 mm



LOCKING OPTIONS

Model	Standardlocking		Optional locking systems		
	Double-bit key lock	Mechanical combination lock	Electronic combination lock	Electronic combination lock*	
MD II-95V	■	■	■	■	■
MD II-130V	■	■	■	■	■
MD II-95R	■	■	■	■	■
MD II-130R	■	■	■	■	■
MD II-95	■	■	■	■	■
MD II-130	■	■	■	■	■

* with emergency key



ACCESSORIES FOR EXTRA CHARGE

Model	Left door hinge	Shelf	Additional fixing hole for designated position Ø = 16 mm	Special fixing kit for concrete floor
MD II-95V	■	■	■	■
MD II-130V	■	■	■	■
MD II-95R	■	■	■	■
MD II-130R	■	■	■	■
MD II-95	■	■	■	■
MD II-130	■	■	■	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



DEPOSIT/BANK EQUIPMENT

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

