



MÜLLER
SAFE



GUN SAFES

GUN SAFE WFS



Model WFS 10



SECURITY LEVEL

S1 according to EN 14450
A according to VDMA 24992 (Conditions May '95)



DESIGN

Body: Single-walled
Door: Double-walled
Hinges: Internal
Door opening angle: 90°
Handle: Protruding 12 mm
Mouting holes: 2 fixing holes in the floor, 2 in the backwall



LOCKING

High security double-bit key lock
2 keys (95 mm)



PAINTING

Light gray, RAL 7035
(special painting according to RAL colors for an extra charge)



GUN SAFE WFS



WFS 6

WFS 10

WFS 15

Model	External dim. in mm			Internal dim. in mm			Adjustment Height (mm)	Door 1 / 2-leaf	Number Gunholder	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth				
WFS 6	1450	280	320	1245	274	255	1215	1-leaf	6	63
WFS 10	1450	430	350	1245	424	284	1215	1-leaf	10	84
WFS 15	1450	630	420	1245	624	260	1215	1-leaf	15	115

Fittings protrude 12 mm

Model	Inner safe external dim. in mm			Inner safe internal dim. in mm		
	Height	Width	Depth	Height	Width	Depth
WFS 6	200			190	274	219
WFS 10	200			190	424	275
WFS 15	200			190	624	314



LOCKING OPTIONS

	Standardlocking	Optional locking systems
Model	 Double-bit key lock	 Electronic combination lock
WFS 6	■	■
WFS 10	■	■
WFS 15	■	■



ACCESSORIES FOR EXTRA CHARGE

Model	Additional fixing hole for designated position Ø = 13 mm	Special fixing kit for concrete floor
WFS 6	 ■	 ■
WFS 10	■	■
WFS 15	■	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



GUN SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

