



MÜLLER  
SAFE



STRONGROOM DOORS

## STRONGROOM DOOR AT VI



Model AT VI-18



### SECURITY LEVEL

Class VI according to EN 1143-1  
certified by ECB-S



### DESIGN

**Door:** Multi-walled  
**Hinges:** External  
**Door opening angle:** 180°  
**Handle/fitting:** Protruding 65 mm



### LOCKING

Two high security double-bit key locks  
each 2 keys (170 mm)



### PAINTING

Light gray, RAL 7035  
(special paint according to RAL colors for an extra charge)



### INSURABLE

Individual agreement



# STRONGROOM DOOR AT VI



Model	External dim. in mm		Wall opening in mm		Door light in mm		Weight (Kg)
	Height	Width	Height	Width	Height	Width	
AT VI-18B	1823	992			1700	800	815
AT VI-20B	2123	1092			2000	900	1000
AT VI-22B	2123	1192			2000	1000	1070

B = block frame

Fittings protrude 65 mm

The frame depth (= wall thickness) is 300 mm as standard. Special dimensions are possible. For wall thicknesses less than 180 mm, fastening by screwing through the frame bushes is not recommended.



## LOCKING OPTIONS

Model	Standardlocking	Optional locking systems	
		<b>Double lock</b> (2 Mechanical combination locks)	<b>Double lock</b> (2 Electronic combination locks)
AT VI-18B	■	■	■
AT VI-20B	■	■	■
AT VI-22B	■	■	■



## ACCESSORIES FOR EXTRA CHARGE

Model	Day-door	Inner blockage system	Left door hinge
AT VI-18B	■	■	■
AT VI-20B	■	■	■
AT VI-22B	■	■	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



STRONGROOM DOORS

**Müller Safe GmbH**

In der Hirtenwiese 6

35745 Herborn, Germany

[www.mueller-safe.de](http://www.mueller-safe.de)

