



MÜLLER
SAFE



DEPOSIT/BANK EQUIPMENT

DEPOSIT SAFE MPT



Model MPT 1



SECURITY LEVEL

Equivalent to **security rating A** to VDMA 24992 (Conditions May '95), but depository slot is not certified



DESIGN

Body: Single-walled
Door: Double-walled
Hinges: Internal
Door opening angle: 90°
Mounting holes: 4 fixing holes in the floor
Insert flap for inserting money or money bags from the front. The insertion flap can be locked with a cylinder lock (2 keys).



LOCKING

High security double-bit key lock
2 keys (65 mm)



PAINTING

Light gray, RAL 7035
(special painting according to RAL colors for an extra charge)



INSURABLE

Individual agreement



DEPOSIT SAFE MPT



MPT 1



MPT 2

Model	External dim. in mm			Internal dim. in mm			Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	
MPT 1	600	250	250	400	240	190	25
MPT 2	600	460	460	400	450	400	45



LOCKING OPTIONS

	Standardlocking	Optional locking systems
	+	
Model	Double-bit key lock	Electronic combination lock*
MPT 1	■	■
MPT 2	■	■

* protrudes approx. 25 mm



ACCESSORIES FOR EXTRA CHARGE

Model	Additional fixing hole for designated position	Special fixing kit for concrete floor
		
MPT 1	■	■
MPT 2	■	■

As of 12/2020 - decorative material not included in the scope of delivery- Technical changes reserved.



DEPOSIT/BANK EQUIPMENT

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

